

# ZS4000



# Bobcat®

*One Tough Animal.*



# OUTWORK. OUTDO. OUTMANEUVER.

**BRING TOUGH TO TURF**

# STABILITY. AGILITY. PROFITABILITY.

With a compact size, extra ground clearance and large drive tires, the ZS4000 gets over and around obstacles and on to the next job.



## ZS4000

MODEL NUMBER	9994001	9994002	9994003	9994004
<b>ENGINE</b>				
Model	Kaw FX600V	Kaw FX651V	Kaw FT730V EFI	Kaw FT730V EFI
Displacement	36.7 cu. in. (603 cc)	44.3 cu. in. (726 cc)	44.3 cu. in. (726 cc)	44.3 cu. in. (726 cc)
Fuel Capacity	5.1 gal. (19.3 L)	6.5 gal. (24.6 L)	6.5 gal. (24.6 L)	6.5 gal. (24.6 L)
Air Filter	Dual Element			
<b>ELECTRICAL</b>				
Charging System	15 amp			
Clutch	125 lbf. (556 N)	200 lbf. (889 N)	200 lbf. (889 N)	200 lbf. (889 N)
<b>DECK</b>				
Mower Deck	DuraDeck™ Cutting System	AirFX™ Cutting System	AirFX™ Cutting System	AirFX™ Cutting System
Leading Edge	Adjustable, Front Lip Standard			
Width	36 in. (914 mm)	48 in. (1219 mm)	52 in. (1320 mm)	61 in. (1549 mm)
Adjustable Anti-Scalp Rollers	3	4	4	7
Cutting Height	1.5-4.5 in. (38-114 mm)			
Blade Tip Speed	17,600 fpm @ 3550 Engine rpm	17,800 fpm @ 3550 Engine rpm	18,586 fpm @ 3550 Engine rpm	18,500 fpm @ 3550 Engine rpm
Discharge Chute	Flexible Molded Polymer			
<b>FRAME</b>				
Front & Rear	Welded 7-gauge Steel; 1.5- x 2.5-inch Steel Tubing			
Machine Length	64.0 in. (1625 mm)			
Machine Weight	800 wet lb.	961 wet lb.	991 wet lb.	1028 wet lb.
<b>TRANSMISSION</b>				
Type	HG ZT-3100 Hydrostatic Transaxles	HG ZT-3400 Hydrostatic Transaxles	HG ZT-3400 Hydrostatic Transaxles	HG ZT-3400 Hydrostatic Transaxles
Pump Displacement	0.6 cu. in. (10 cc)	0.7 cu. in. (12 cc)	0.7 cu. in. (12 cc)	0.7 cu. in. (12 cc)
Oil Capacity	1.0 gal. (4 qt)			
Forward Speed	0-9.0 mph (0-14.4 km/hr.)	0-10.5 mph (0-16.8 km/hr.)	0-10.5 mph (0-16.8 km/hr.)	0-10.5 mph (0-16.8 km/hr.)
Reverse Speed (mph)	0-3.5 mph (0-5.6 km/hr.)			
<b>WHEELS</b>				
Drive Wheel Size	20 x 8.0-10	23 x 8.5-12	23 x 10.5-12	23 x 10.5-12
Front Caster Wheel Size	11 x 6.0-5	13 x 6.5-6	13 x 6.5-6	13 x 6.5-6
Caster Arm Attachment	Bolt-On			
<b>OPERATOR PLATFORM</b>				
Adjustment	Flip Up and Latch			
Rider Pad	Tethered, Removable for Service			
Vibration Isolation	Dampened			

