

GM2800-B ROTARY MOWER OVERVIEW

Specifications			
Model		GM2800B	
Dimensions	Total length		370 cm
	Total width	During operation	300 cm
		During transport	230 cm
	Total height	Roof	230 cm
Handle		165 cm	
Weight		2,030 kg	
Minimum turning radius		320 cm	
Engine	Model	Kubota V2403-M-T	
	Type	Vertical water-cooled 4-cycle diesel engine with turbocharger	
	Total displacement	2,434 cm ³ (2.433 L)	
	Maximum output	41.7 kW(56.7 PS)/2,600 rpm	
Fuel tank capacity		Diesel 51.0 dm ³ (51.0 L)	
Fuel consumption		208 g/kW.h (rated output)	
Quantity of engine oil		10.0 dm ³ (10.0 L)	
Mowing width		280 cm	
Mowing height		20 - 91.5 mm	
Drive		HST, 2WD/4WD selectable	
Speed (HST)	Forward	0 - 16.0 km/h	
	Reverse	0 - 9.0 km/h	
Speed (Mechanical)		-	
Efficiency		20,160 m ² /h (9.0 km/h x mowing width x 0.8)	
Maximum inclination for operation		15 degrees	
Tyre size	Front wheel	29 x 14.00 - 15	
	Rear wheel	20 x 12.00 - 10	
Tyre pneumatic pressure	Front wheel	150 kPa (1.5 kgf/cm ²)	
	Rear wheel	140 kPa (1.4 kgf/cm ²)	
Battery		105D31R	

*The factory default maximum engine rpm is 2,400 rpm.

GM2800-B
ROTARY MOWER

THE PERFECTION OF NATURE

BARONESS BARONESS



For more information please contact:
AUSTRALIA
 Kubota Tractor Australia
 25 - 29 Permas Way, Truganina,
 Victoria, 3029 Australia
 Freecall: 1800 334 653
 kubota.com.au

NEW ZEALAND
 CB Norwood Distributors Ltd
 888 Tremaine Avenue, Palmerston North,
 0800 New Zealand
 Call: 06 356 4920
 kubota.co.nz

For Earth, For Life
Kubota

THE CRAFT OF PRECISION ENGINEERING

OPERATOR COMFORT AND PROTECTION

- / A protection net and weather canopy enhance operator safety.
- / Comfortable seating position with excellent all round visibility.

KUBOTA DIESEL ENGINE

- / Powerful and reliable, 4-cycle Kubota diesel engine with turbocharger.
- / Easy maintenance access.
- / No complicated electronics or computer analysis system.

ACCESSIBLE AND EFFICIENT COOLING SYSTEM

- / Large radiator and oil cooler for efficient temperature control.
- / Large access door for fast and simple maintenance.
- / Drop down oil cooler for easy cleaning.

SHORT WHEEL BASE

- / A tight turning circle for outstanding maneuverability.
- / Light power steering.

SWING-OUT REAR CUTTING UNITS

- / Easy access for making adjustments, maintenance and cleaning.

SUPERIOR TRACTION AND SLOPE PERFORMANCE

- / Selectable 2WD or 4WD on demand as standard.
- / 4 stage 'Traction Assist' weight transfer system.
- / Differential locks.
- / Light footprint with minimal turf marking.

QUICK AND POSITIVE HEIGHT OF CUT ADJUSTMENT

- / All 5 decks can be changed in under 10 minutes.
- / Height range from 20mm to 91mm.
- / Suitable for rough or semi rough surfaces, parks and gardens, golf and sports fields.
- / Perfect for cutting fairways during the muddy winter months.

UNIQUE DECK PAN DESIGN

- / Spiral deck pan design provides excellent grass clippings dispersal and a very clean finish.
- / Full-length rear rollers allow cutting over a bunkers edge.
- / Cutting decks protrude outside of the wheel line, allowing for a close cut near trees or over a bunkers edge.
- / Full-length rear rollers minimize scalping and provide a good stripe for winter fairway work.
- / Deep, strong deck pans built to manage long thick grass.

LONG LIFE BLADES

- / Made from an alloy of hardwearing and tough metals.
- / Lasts up to 5 times longer than standard blades.
- / Stays sharper for longer enhancing grass condition and appearance.
- / Reduces maintenance costs and machine downtime.

TRANSFORMING
NATURE IS AN ART

BARONESS

GM2800-B ROTARY MOWER

The new Baroness GM2800-B is engineered to the most exacting Japanese standards and is uncompromising in delivering an unmatched quality of cut and finish. Perfection is at the heart of this high performance and reliable rotary mower.

For Earth, For Life
Kubota

